



GOLD CONCENTRATE

Antifreeze / Coolant

iLast Premium Light Duty Gold Concentrate AntiFreeze

Used as directed, offers superior performance in virtually every light duty application. The proprietary inhibitor package is low silicate and phosphate and 2-EH free. Can be used as a top-off but to achieve maximum protection a complete flush and fill should be performed. iLast Premium Antifreeze provides protection against:

- Freeze-up
- Boil Over
- Scale Build Up
- Rusting
- Sludge/Clogging
- Corrosion

Advantages

- Meets Light Duty ASTM D-3306
- Hybrid chemistry with long-life technology.
- Recommended for use in all domestic and European models.
- Phosphate free and low silicate - the choice for Japanese and Korean models.
- Light Duty - 5 years/150,000 miles
- Compatible with any color antifreeze.
- For safety purposes all iLAST antifreeze is blended with a bittering agent.

Specifications

iLast Gold Concentrate is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- ASTM D-3306
- GM 1825M
- Chrysler MS 7170
- JIS K 2234
- GM 1899M
- Ford ESE-M97B44-A



TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD
Appearance	Visual	Gold/Yellow
Specific Gravity at 60/60°F	1.085-1.150	D 1122
Freeze Point, at 50% max	-34°F	D-3321
pH at 50% Solution	8.5-10.0	D-1287
Reserve Alaklinity min.	6	D-1121
Foam Test	150ml/5 sec	D-1881

FREEZE/BOIL PROTECTION CHART	% of Cooling System capacity	PROTECTS FROM	
		Freezing Down to	Boiling Up to*
Using a 15 PSI Pressure Cap	40	-10 °F	259 °F
	50	-34 °F	265 °F
	60	-62 °F	270 °F

Cooling System Capacity in Quarts	Quarts of Antifreeze Required for Protection to Temperature (°F) Shown										
	3	4	5	6	7	8	9	10	11		
8	-7	-34									
9	0	-21	-50								
10	4	-12	-34	-62							
11	8	-6	-23	-47							
12	10	0	-15	-34	-57						
13	3	-9	-25	-45							
14	6	-5	-18	-34	-54						
15	8	0	-12	-26	-43	-62					
16	10	2	-8	-19	-34	-52					
17		5	-4	-14	-27	-42	-58				
18		7	0	-10	-21	-34	-50	-62			
19			9	2	-7	-16	-28	-42	-56		
20			10	4	-3	-12	-22	-34	-48		

For best overall protection, solution strengths within the YELLOW color band are recommended.

50% SOLUTION RECOMMENDED TO OBTAIN MAXIMUM PROTECTION. DO NOT EXCEED 70% CONCENTRATION OF ANTIFREEZE.